



ALTV244UL, ALTV244ULCB UL Listed AC CCTV Power Supply

Rev. DSALTV244UL - A24F

Overview



- These Altronix AC Wall Mount CCTV Power Supplies provide 24VAC or 28VAC distributed via four (4) fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV244UL

- Four (4) fuse protected outputs.
- Outputs are rated @ 3.5 amp.

ALTV244UL3

ALTV244UL w/3-wire Line Cord.

ALTV244ULCB

- Four (4) Class 2 Rated PTC protected power limited outputs.
- Outputs are rated @ 2.5 amp.

ALTV244ULCB3

ALTV244ULCB w/3-wire Line Cord.

Specifications

- Input 115VAC, 50/60Hz, .9 amp.
 - 24VAC @ 3.5 amp (85VA) or 28VAC @ 3 amp (85VA) supply current.
 - Main fuse rated @ 5 amp/250V.
 - Power ON/OFF switch.
 - Surge suppression.
 - AC power LED.
 - Spare fuse(s) provided (all models w/primary and/or secondary fuses).
 - Unit maintains camera synchronization.
 - Ease of installation saves time and eliminates costly labor.
- Product weight:
 - ALTV244UL: 6.4 lbs.
 - ALTV244UL3: 6.7 lbs.
 - ALTV244ULCB: 6.5 lbs.
 - ALTV244ULCB3: 6.8 lbs.
 - Shipping weight:
 - ALTV244UL: 7.0 lbs.
 - ALTV244UL3: 7.3 lbs.
 - ALTV244ULCB: 7.0 lbs.
 - ALTV244ULCB3: 7.3 lbs.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



Canadian Standard Association



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions

8.5"H x 7.5"W x 3.5"D

