



R248ULI, R248ULCBI UL Listed Isolated Rack Mount CCTV Power Supply

Rev. DSR248ULI - B21F

Overview



- These Altronix Isolated Rack Mount CCTV Power Supplies provide 24VAC distributed via isolated fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

R248ULI

- Eight (8) isolated fuse protected outputs.
- Outputs are rated @ 3.5 amp.

R248ULCBI

- Eight (8) isolated Class 2 Rated PTC protected power limited outputs.
- Outputs are rated @ 2.5 amp.

Specifications

- 24VAC output.
- 12.5 amp (300VA) supply current.
- Eight (8) 1.6 amp isolated outputs.
- Input 115VAC 50/60Hz, 2.7 amp.
- Individually isolated outputs.
- Illuminated power disconnect circuit breaker with manual reset.
- Removable terminal blocks w/locking screw flanges.
- 3-wire grounded line cord.
- Individual power LEDs.
- Spare fuse(s) provided for all models.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.
- 2U rack mount chassis for use in standard EIA 19" rack.
- Product weight:
 - R248ULI: 16.1 lbs.
 - R248ULCBI: 16.1 lbs.
- Shipping weight:
 - R248ULI: 17.1 lbs.
 - R248ULCBI: 17.1 lbs.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions

3.25"H x 19.125"W x 8.5"D

View from back

