



### Overview



- This unit will convert a 115VAC / 60Hz input, into a regulated 12VDC or 24VDC output at 6 amp continuous supply current (see specifications).

### Specifications

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• 12VDC or 24VDC selectable output.</li> <li>• 6 amp of continuous supply current output.</li> <li>• Input 115VAC 50/60Hz, 1.45 amp input.</li> <li>• Filtered and electronically regulated outputs.</li> <li>• Short circuit and thermal overload protection.</li> <li>• Built-in charger for sealed lead acid or gel type batteries.</li> <li>• Maximum charge current .7 amp.</li> <li>• Automatic switch over to stand-by battery when AC fails (zero voltage drop).</li> </ul> | <ul style="list-style-type: none"> <li>• Power ON/OFF switch.</li> <li>• AC input and DC output LED indicators.</li> <li>• Power supply, enclosure, cam lock &amp; battery leads.</li> <li>• Enclosure:             <ul style="list-style-type: none"> <li>- Combination knockouts are 1/2" and 3/4"</li> <li>- Accommodates up to two (2) 12VDC/7AH batteries.</li> </ul> </li> <li>• Product weight: 7.8 lbs.</li> <li>• Shipping weight: 8.8 lbs.</li> </ul> |
|--|---|

### Enclosure Dimensions

13"H x 13.5"W x 3.25"D

