



## Overview

- These Altronix outdoor CCTV Power Supplies provide power via four (4) protected outputs for CCTV Cameras, heaters and other video accessories.

### **WPTV244175UL**

- 24VAC @ 7 amp (170VA) or 28VAC @ 6.25 amp (175VA).
- Input 115VAC 50/60 Hz rated @ 1.76 amp.
- One (1) fuse protected non-power limited output rated @ 10 amp/250V.

### **WPTV244300UL**

- 24VAC @ 12.5 amp (300VA) or 28VAC @ 10 amp (280VA).
- Input 115VAC 50/60 Hz rated @ 2.7 amp.
- One (1) fuse protected non-power limited output rated @ 15 amp/32V.

## Specifications

- Input 115VAC 50/60 Hz.
- Four (4) protected outputs:
  - One (1) fuse protected non-power limited output.
  - Three (3) Class 2 Rated PTC protected power limited outputs rated @ 2.5 amp.
- Illuminated power disconnect circuit breaker with manual reset.
- Surge suppression.
- AC power LED.
- Spare fuses provided.
- Unit maintains camera synchronization.
- Ease of installation saves time & eliminates costly labor.
- NEMA 4 Rated enclosure for outdoor use.

## Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



European Conformity



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

**Enclosure Dimensions**

12"H x 8"W x 6"D

