

AXIS P1425-LE Mk II Network Camera

Compact, cost-effective HDTV surveillance with OptimizedIR

With Lightfinder and WDR – Forensic Capture, the AXIS P1425-LE Mk II bullet camera provides excellent image quality in HDTV 1080p resolution, even in complex light conditions. Axis' OptimizedIR automatically illuminates any scene taking place in complete darkness. The camera features Corridor Format, pixel counter, remote focus and zoom, as well as P-Iris control – ensuring optimal depth of field, resolution, image contrast and clarity. The I/O port can be used for notification to an alarm panel or control of a relay. Axis Zipstream technology significantly reduces bandwidth and storage requirements. The outdoor-ready camera comes with an adjustable weather shield.

- > [Lightfinder and WDR – Forensic Capture](#)
- > [Axis Zipstream technology](#)
- > [HDTV 1080p at up to 60 fps](#)
- > [Built-in IR LEDs with OptimizedIR, 20 meters \(66 feet\)](#)
- > [I/O support and Edge Storage](#)



AXIS P1425-LE Mk II Network Camera

Camera		
Image sensor	Progressive scan CMOS 1/2.8"	
Lens	3–10.5 mm, F1.4 Horizontal field of view 93°–33° Vertical field of view 50°–18° Varifocal, Autofocus, Remote focus and zoom, P-Iris control, IR corrected	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 0.16 lux at F1.4, 25/30 fps Color: 0.32 lux at F1.4, 50/60 fps B/W: 0.03 lux at F1.4, 25/30 fps B/W: 0.06 lux at F1.4, 50/60 fps 0 lux with IR illumination on	
Shutter time	1/66500 s to 1 s	
Video		
Video compression	H.264 High, Main and Baseline profiles (MPEG-4 Part 10/AVC) Motion JPEG	
Resolution	HDTV 1080p 25/30 fps (WDR): 1920x1080 to 160x90 HDTV 1080p 50/60 fps (no WDR): 1920x1080 to 160x90 Meets relevant parts of SMPTE 274M (HDTV 1080p)	
Frame rate	Up to 50/60 fps (50/60 Hz, no WDR) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	
Image settings	Manual shutter time, Compression, Color, Brightness, Sharpness, White balance, Exposure control, Exposure zones, Fine tuning of behavior at low light, Text and image overlay, Privacy masks, IR illumination Wide Dynamic Range - Forensic Capture: Up to 120 dB depending on scene, Mirroring of images Rotation: 0°, 90°, 180°, 270°, including Corridor Format	
Pan/Tilt/Zoom	Digital PTZ	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log	Pre- and post-alarm video buffering WDR mode PTZ control, Overlay text IR illumination
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH LLDP	Built-in installation aids Pixel counter, Remote zoom (3.5x optical), Remote focus
System integration		Data streaming Event data
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com ONVIF [®] Profile S and ONVIF [®] Profile G, specification at onvif.org	General
Analytics	Included AXIS Video Motion Detection Supported AXIS Digital Autotracking, AXIS Perimeter Defender, AXIS Cross Line Detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/accp	Casing IP66, IP67- and NEMA 4X-rated casing (polyester polycarbonate blend)
Event triggers	Analytics Detectors: Day/Night Mode, Live Stream Accessed, Tampering Hardware: Network, Temperature Input Signal: Manual Trigger, Virtual Inputs Storage: Disruption, Recording System: System Ready Time: Use Schedule, Recurrences	Sustainability PVC free
Event actions	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap External output activation Video recording to edge storage	Memory 512 MB RAM, 256 MB Flash
		Power Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical: 4.6 W, max 11 W
		Connectors RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin terminal block for 1 alarm input and 1 output
		IR illumination Optimized IR, highly efficient LEDs with adjustable intensity and angle of illumination. Range up to 20 m (66 ft)
		Storage Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
		Operating conditions -30 °C to 50 °C (-22 °F to 122 °F) Humidity 10–100% RH (condensing)
		Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
		Approvals EN 61000-6-1, EN 61000-6-2, EN 50121-4, IEC 62236-4, EN 50581, EN 55024, EN 55032 Class A, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN-32 Class A, KN-35, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, IEC/EN 62471, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78, IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK08, NEMA 250 Type 4X, IEC 60825-1
		Weight With weather shield: 800 g (1.75 lb)
		Dimensions Ø132 x 260 mm (Ø5 3/16 x 10 1/4 in)
		Included accessories Mounting bracket, Drill template, Installation Guide, Windows decoder 1-user license AXIS Weather Shield L
		Optional accessories AXIS T94F01M J-Box/Gang Box Plate AXIS T91A47 Pole Mount AXIS T94P01B Corner Bracket AXIS T94F01P Conduit Back Box AXIS Weather Shield K Axis PoE Midspans For more accessories, see www.axis.com
		Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/vms
		Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		Warranty Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
		a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).</i>
		Environmental responsibility: www.axis.com/environmental-responsibility