

# WRT-P-5201 Series

Wisenet WAVE Network Video Recorder



The WRT-P-5201W series dual purpose Wisenet WAVE server and client is built into a compact mini-tower form factor running Windows 10 IoT Enterprise LTSC or Ubuntu Linux 18.04 LTS. This ready to deploy solution can manage up to 470 Mbps of recording throughput and up to 36TB of storage for a single site or as an addition to your existing Wisenet WAVE system.

Each is pre-configured with Wisenet WAVE VMS and preloaded with 4 Professional licenses to ensure quick and easy deployment with minimum setup time

## Key Features

- Preloaded and configured with Wisenet WAVE video management system & tools
- Up to 36TB of Raw Storage
- 470 Mbps of recording throughput
- Includes (4) four Wisenet WAVE Professional licenses
- Includes USB mouse and keyboard
- 5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty
- Supports Wisenet and ONVIF conformant IP cameras



WRT-P-5201W / WRT-P-5201L

SYSTEM	
Video Management Software	Wisenet WAVE
Recording Bandwidth	Up to 470 Mbps
Pre-loaded Licenses	4 x Wisenet WAVE Professional license
OS Drive Bays	1 x 256GB SSD (internally mounted)
Data Drive Bays	3x 3.5" SATA HDDs
Data Storage	Up to 36TB raw storage
Network Interface	2 x RJ-45, Gigabit Ethernet
Processor	1 x Intel® Core® i5 10 <sup>th</sup> Generation
Memory	16GB DDR4
Operating System	Windows 10 IoT Enterprise LTSC / Ubuntu Linux 18.04 LTS
Video Outputs	2x DisplayPort with 1 x DisplayPort to HDMI adapter
USB Ports	Rear (4) USB 3.0, (2) USB 2.0; Front (1) USB 3.0, (2) USB 2.0, (1) USB 3.0 Type-C
Other Ports	3.5mm audio output, PS2 Keyboard & Mouse, Serial
Keyboard & Mouse	Included

MECHANICAL / ELECTRICAL / ENVIRONMENTAL		
Mechanical	Form Factor	Tower
	Color / Material	Black / Metal
	Dimensions (HxWxD)	13.19" x 6.95" x 13.58" (33.5cm x 17.7cm x 34.5cm)
	Weight	24 lbs (10.8 kg)
Electrical	Power Supply	460W 80 Plus Gold
	Power Input	100 ~ 240V AC
	Power Consumption	Maximum 550W
Environmental	Operating Temperature	32°F ~ 95°F (0°C ~ 35°C)
	Storage Temperature	-40°F ~ 149°F (-40°C ~ 65°C)
	Operating Humidity	10% to 80% RH non-condensing
Certification	UL, cUL, CB, FCC, 80 Plus Gold	

\* Weight is on chassis without HDDs  
 \* The latest product information / specification can be found at [www.hanwhasecurity.com](http://www.hanwhasecurity.com)  
 \* Bandwidth performance figures based on performance testing by Hanwha Techwin using Wisenet WAVE

