



## Multitechnology credentials



## Overview

Schlage® multi-technology credentials are extremely flexible. Particularly useful during a transition from magnetic stripe and proximity technology to smart technology, this card can be read by magnetic stripe, proximity and smart readers. This allows customers to economically migrate to the latest smart technology at their own pace.

Schlage multi-technology credentials contain both 125 kHz proximity and 13.56 MHz contactless smart card capability in one unit, and are available in the newest technologies of today, including MIFARE Classic®, MIFARE Plus® and MIFARE® DESFire® EV1.

## Features and benefits

- Open architecture design is built on ISO 14443A standards, providing for a faster data transfer speed
- Only available in ISO style cards
- Utilizes 125 kHz proximity and MIFARE Classic®, MIFARE Plus® or MIFARE® DESFire® EV1
- Custom artwork and laser engraving available









25 kHz/13.56 MHz r	multi-technology cre	edentials		
lodel number	9951	9958	9691T	5951
redential type	ISO glossy white <sup>1</sup>	ISO glossy white <sup>1</sup>	Thin keyfob	ISO glossy white <sup>1</sup>
redential technology;	Proximity/MIFARE	Proximity/MIFARE	Proximity/MIFARE	Proximity/MIFARE
60 standard	Classic; ISO 14443	Classic; ISO 14443	Classic; ISO 14443	Plus SE; ISO 14443
agnetic stripe available	Yes²	Yes <sup>2</sup>	No	Yes <sup>2</sup>
imensions (H x W x D)	3.37" x 2.125" x 0.033"	3.37" x 2.125" x 0.033"	1.77" x 1.18" x 0.06"	3.37" x 2.125" x 0.033
lot punch (printed guide)	Vertical or horizontal	Vertical or horizontal	Keyring	Vertical or horizontal
lemory capacity;	1K byte/8k bit;	4K byte/32k bit;	1K byte/8k bit;	1K byte/8k bit
oplication sectors	16 sectors	40 sectors	16 sectors	
	16 sectors	•	16 sectors	







125 kHz/13.56 MHz mu	ılti-technology credentials		
Model number	5940	5691T	8920/8940/8980
Credential type	ISO glossy white <sup>1</sup>	Thin keyfob	ISO glossy white <sup>1</sup>
Credential technology;	Proximity/MIFARE Plus S;	Proximity/MIFARE Plus SE;	Proximity/MIFARE DESFire EV1;
ISO standard	ISO 14443	ISO 14443	ISO 14443
Magnetic stripe available	Yes <sup>2</sup>	No	Yes <sup>2</sup>
Dimensions (H x W x D)	3.37" x 2.125" x 0.033"	1.77" x 1.18" x 0.06"	3.37" x 2.125" x 0.033"
Slot punch (printed guide)	Vertical or horizontal	Keyring	Vertical or horizontal
Memory capacity;	4K byte/32k bit	1K byte/8k bit	2K byte/8k bit;
application sectors			4K byte/32k bit;
			8K byte/64k bit

<sup>1</sup> ISO glossy white style credentials are made from composite material, are printable, and can include a magnetic stripe as an option

Allegion, the Allegion logo, Schlage and the Schlage logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

## **About Allegion**

Allegion (NYSE: ALLE) is a global pioneer in safety and security, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion produces a range of solutions for homes, businesses, schools and other institutions. Allegion is a \$2 billion company, with products sold in almost 130 countries. For more, visit www.allegion.com.



 $<sup>2.</sup> Add \, M1 \, to \, the \, model \, number \, for \, a \, magnetic \, stripe \, when \, ordering. \, Vertical \, slot \, punch \, not \, available \, on \, magnetic \, stripe \, cards.$